

LEVEL
IIIA



THREATS



FITS INSIDE
MOST
BACKPACKS
WEIGHS ONLY
8.2 OZ

TETRA

LEVEL IIIA | SOFT ARMOR INSERT

AD AREAL DENSITY: **1.17 psf**

T THICKNESS: **0.275"**

F FLEXIBILITY: **Medium**

S TEMPLATE SIZE: 12" x 15"

PA PRODUCT APPLICATION:
Backpack Insert

M TYPE OF MATERIALS:
3000D Twaron® Microlam
Twaron® 2-Ply Unidirectional Fabric

C TYPE OF CONSTRUCTION:
W.R.A.P.™ — Water Repellent Armor
Perimeter (Patent Pending)

PC TYPE OF PROTECTIVE COVER:
Brookwood 70D with Laminated Polyurethane

PS TYPE OF PROTECTIVE SEAL:
Sonobond Ultrasonic Bond

ST SPECIAL THREAT TESTING*:

- 2 grain RCC V50: 3013 fps
- 4 grain RCC V50: 2545 fps
- 16 grain RCC V50: 2225 fps
- 17 grain FSP V50: 2077 fps
- .44 Mag V50: 1615 fps
- .357 Sig V50: 1735 fps
- FN SS197 40 grain V0
- Win SXT 9mm +P+ V0
- 7.62x25 Tokarev 85 grain V0
- .357 SIG Win SXT 125 grain V0
- Speer GD .357 Mag V0

*Special Threat Testing Conducted in accordance with an abbreviated and modified NIJ 0101.06 and AFCI Special Threat Testing Protocol.

